

ZLT P10P 4G CPE Indoor Type



Specification

Access Technology	TD-LTE/LTE-FDD WCDMA(HSPA+,HSDPA,HSUPA) GGE(GSM/GPRS/EGPRS)
Frequency	GGE:850/900/1800/1900MHz TD-LTE:Band38(2570-2620MHz) Band39(1880-1920Mhz) Band40(2300-2400Mhz) Band41(2496-2690Mhz) WCDMA:Band1/2/5/8 LTE FDD:Band3/7/8/17

(Frequency can be customized according to requirement)

Main Function

Support 2G/3G/4G network connection
WLAN Function, easy to expand wireless network
Prevent loiter network, multi wireless safety ensuring
IP broadband control, ensure the speed
Improve transmission efficiency, enlarge coverage area,
Improve stability by dual antennas
Support WEB page management, easy to install
Support network traffic statistics
Support more than 10 WIFI device online simultaneously
Support VPN
Support dual uplink (mobile network and RJ45 Ethernet)
Support dual TR069 and SNMP

Access ability	LTE:support dual stream;support CAT4:DL:150M bps UL:50M bps support bandwidth 10,15,20MHZ,2*2DL SU-MIMO WCDMA:HSDPA,downlink speed up to 21 Mbps;HSUPA:uplink speed up to 5.76 Mbps GGE:R4 standard,also support R9 inter-operation GPRS:Class12,maximum transmission speed 85.6k bit/s EDGE:Class12,maximum transmission speed 236.8k bit/s
Sim/Usim	support SIM card and USIM card support 1.8V and 3V voltage SIM card and USIM card
WIFI mode	Wi-Fi 2.4GHz support 802.11b/g/n 2*2 antenna
Size	152X70X180mm