

Model: HT-WR958N

300M Wireless b/g/n 4p Router



Feature

- Wireless N speed up to 300Mbps makes it ideal for bandwidth consuming or interruption sensitive applications like video streaming, online gaming
- Easily setup a WPA encrypted secure connection at a push of the WPS button
- WDS wireless bridge provides seamless bridging to expand your wireless network
- QoS function assures and multimedia streaming
- Features parental control function managing the internet access of children or employee's computer
- Supports virtual server, special application and DMZ host ideal for creating a website within your LAN
- Offers Auto-mail function for system log, convenient for managing the router
- Backward compatible with 802.11b/g products
- Easy Setup Assistant provides quick & hassle free installation
- Sleek exterior, can be mounted on a wall or placed horizontally on a table or desk

SPECIFICATION

HARDWARE FEATURES	
Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Button	WPS/Reset Button Power JACK
External Power Supply	5VDC / 1A
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Antenna	2*5dBi Fixed Omni Directional Antenna
WIRELESS FEATURES	
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 300Mbps(dynamic)

WIRELESS FEATURES	
	11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
EIRP	<20dBm(EIRP)
Reception Sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK
SOFTWARE FEATURES	
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
DHCP	Server, Client, DHCP Client List, Address Reservation
Quality of Service	WMM, Bandwidth Control
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Management	Access Control Local Management Remote Management
OTHERS	
Package Contents	Wireless N Router HT-WR958N Power supply unit Quick Installation Guide
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing